



SPECIFICATION

RATING	DC 30V 0.5A
CONTACT RESISTANCE	30mΩ Max
INSULATION RESISTANCE	DC 500V 100mΩ MIN
WITHSTAND VOLTAGE	500V 1 MINUNT
TORQUE	1 TO 2 SECTION 0.8Kg±0.2Kg OVER SECTION 2.5Kg±1Kg
SWITCH TYPE	SHORTING (make before brake)

A	2	C1-1	I	2	C1-9	Q	2	C1-17
B	2	C1-2	J	2	C1-10	R	2	C1-18
C	2	C1-3	K	2	C1-11	S	2	C1-19
D	2	C1-4	L	2	C1-12	T	2	C1-20
E	2	C1-5	M	2	C1-13	U	2	C1-21
F	2	C1-6	N	2	C1-14	V	2	C1-22
G	2	C1-7	O	2	C1-15	W	2	C1-23
H	2	C1-8	P	2	C1-16	X	2	C1-24

△				MODEL	RT2024		A
TOLERANCES		DIMENSION	SCALE	DRAWN BY	CHECKED BY	APPROVED BY	DRAWING NO.
less than 10	± 0.3	m/m	/	DA18			RT2024-1.2
above 10 - 30	± 0.5						
above 30 - 100	± 1.0						
angular dimension	± 5 °						Switch